

# MARICOPA COUNTY Department of Transportation

**MEMORANDUM** 

**Date:** January 2, 2008

**To:** MAG Specifications and Details Committee

From: Robert Herz, MCDOT Representative

Subject: 317 Asphalt Milling Case 08- 02

PURPOSE: Incorporate specifications from MCDOT's Supplement into the MAG specifications

as requested by the MAG Standards & Details Consolidation Subcommittee.

REVISION: Add to Part 300: Section 317 Asphalt Milling.

2901 West Durango Street Phoenix, Arizona 85009 Phone: 602-506-4760 Fax: 602-506-5969

### **SECTION 317**

### ASPHALT MILLING

### 317.1 DESCRIPTION:

The work under this Section shall consist of milling existing asphalt concrete pavement where shown on the Plans or requested by the Engineer.

## 317.2 CONSTRUCTION REQUIREMENTS:

Contractor is responsible for locating all milling hazards on and below the surface within the area to be milled including areas requiring special milling. Special milling is not a separate pay item and shall be paid for as Asphalt Milling.

The milling cut depth shall be the depth indicated on the Plans plus or minus 1/8 inch. Contractor shall remove the milled material and sweep the roadway clean with a power pick-up broom to the satisfaction of the Engineer.

Asphalt pavement adjacent to manholes, valve boxes, small radius curbs and other fixed objects that produce confined areas shall be removed with milling equipment specifically designed to operate in restricted areas. The equipment shall be capable of removing asphalt concrete of the specified thickness without damage to, or displacement of, the adjacent object(s).

The work shall result in a clean milled surface to the specified depth for the area indicated by the construction documents including the areas immediately around and next to any individual hazard within the area to be milled.

The Contractor shall be responsible for continually checking the milling operation to determine that the proper depth of milling has been achieved, that the proper profile and cross slope are achieved, and that the surface texture is (a) free from longitudinal ridges, and (b) has a uniform pattern.

### 317.3 MEASUREMENT AND PAYMENT:

Measurement for Asphalt Milling will be by the square yard and shall only include areas milled to the required depth and cross section.

Payment for Asphalt Milling at the contract unit price shall be full compensation for the work, complete-in-place, including all asphalt milling, milling around structures, removal and disposal of milled materials, and sweeping.